

Exclusively from Safety Direct America!

SparkleTuff™ Anti-Slip FLOOR COATING



At last you can have the flooring you love without fear of injuries due to slips, *WET OR DRY!* Tile, marble, granite, epoxy, polyurea, polyaspartic, wood, vinyl, mosaic, glass, etc. can meet and exceed OSHA- and ADA-compliant slip resistance (or DCOF) levels.

SparkleTuff™ Anti-Slip is safe and easy to apply and is fully compatible with non-abrasive cleaning methods. **SparkleTuff™ Anti-Slip Floor Coating** has outstanding wear and chemical resistance, including resistance to acids and alkalis, and can also be used for underwater applications. It has excellent weathering and dirt pickup resistance and strong anti-corrosive characteristics.

SparkleTuff™ Anti-Slip Floor Coating retains its transparency and gloss far better than practically any other floor topcoat, including the best-of-breed epoxies and polyurethanes. **SparkleTuff™ Anti-Slip** does not require burnishing, and so less aggressive cleaning with safer cleaning agents and softer bristle pads or brushes is possible.

SparkleTuff™ Anti-Slip provides an abrasion-, stain- and water-resistant glossy finish that helps protect the coated surface from wear and damage while greatly reducing regular and costly maintenance such as stripping, polishing and waxing in a range of facilities including hospitals, swimming pools, schools, airports, restaurants, markets, hotels and resorts. When it is time to re-coat, simply add a fresh coat right over the existing coat. Quick and easy, once every 5-10 years depending on foot traffic. Properly applied and maintained, it will keep its slip resistance even when millions of people have walked over it! **It's been in some high-traffic areas for eight years now without the need to re-coat ever!!**

Sustainable — **SparkleTuff™ Anti-Slip** is a great way to make facilities more “green” compliant. Stripping, burnishing and re-waxing floors emits air pollutants, creates chemical by-products and waste and consumes precious commodities such as electricity and water.

SparkleTuff™ Anti-Slip, with its unique chemistry and composition, ease of use and outstanding durability is now the obvious coating of choice. Unlike other two-part coatings it has low VOC and odor.

SparkleTuff™ Anti-Slip has a 75 minute working time after mixing. A 6-8 hour cure is recommended. At this time the coating will have hardened sufficiently to permit foot traffic and will have developed liquid- and stain-resistant properties. The chemical integration of the resin matrix will continue over the next 48 to 72 hours, at which time **SparkleTuff™ Anti-Slip** will achieve its optimal abrasion-, chemical- and weather-resistant properties!

IMPORTANT: Designed to be mixed with other components. The mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions. **KEEP OUT OF REACH OF CHILDREN.** Refer to Safety Data Sheet for additional health and safety information.



www.SafetyDirectAmerica.com

1-949-933-6971 USA

info@SafetyDirectAmerica.com